



MFD. BY FORD MOTOR CO.

DATE: 08/13

GVWR/PNBV: 3493 KG (7700 LB)



FRONT GAWR/PNBE AV / REAR GAWR/ PNBE AR
1769 KG (3900 LB) 1837 KG (4050 LB)

WITH/AVEC TIRES/PNEUS

LT275/65R18C 113/110S

LT275/65R18C 113/110S

18X7.5J

RIMS/JANTES 18X7.5J



AT/A kPa/PSI/LPC 275/40

COLD/A FROID

275/40

/JUMEELES

VIN: 1FTFW1ET1DKF68415

TYPE: TRU/CAM

COMPLIES: ICES/NMB-002

F0023

T0662



EXT PNT:

YZ

RC: B4

DSO:

WB

INT TR

TP/PS

R

AXLE

TR

SPR

157

MS

D

L6

6

VVGG

2201308214758

UCT

▽5U5A-1520472-BA



TIRE AND LOADING INFORMATION

RENSEIGNEMENTS SUR LES PNEUS ET LE CHARGEMENT

SEATING CAPACITY
NOMBRE DE PLACES

TOTAL

6

FRONT
AVANT

3

REAR
ARRIERE

3

The combined weight of occupants and cargo should never exceed
Le poids total des occupants et du chargement ne doit jamais dépasser

744 kg or 1641 lbs.
kg ou lb.

▽5U5A-1532-AA (TLC)

1FTFW1ET1DKF68415

TIRE
PNEU

SIZE
DIMENSIONS

COLD TIRE PRESSURE
PRESSION DES
PNEUS A FROID

FRONT
AVANT

LT275/65R18C 113/110S

275 KPA, 40 PSI

REAR
ARRIERE

LT275/65R18C 113/110S

275 KPA, 40 PSI

SPARE
DE
SECOURS

LT275/65R18C 113/110S

275 KPA, 40 PSI

SEE OWNER'S
MANUAL FOR
ADDITIONAL
INFORMATION

VOIR LE MANUEL
DE L'USAGER
POUR PLUS DE
RENSEIGNEMENTS

